

CUSTOM TAILORING MEASUREMENT FORM

Use the empty space in each column to fill in the appropriate measurement in inches.

Be sure to wear your best fitted dress shirt and dress pants or khaki pants. No jeans, or athletic wear, make sure to empty your pockets.

Forward your completed measurements to us at – acesamofficial@gmail.com

Be sure to also send us your height in feets/inches, and your weight in pounds (lbs), along with three full length photographs of a front, side and back profile.

	BODY PART	IMAGE	INSTRUCTION	VALUE – IN INCHES
1.	NECK		MEASURE AROUND THE LOWER PART OF THE NECK, PLACING A FINGER BETWEEN MEASURING TAPE AND NECK.	
2.	SHOULDERS		MEASURE YOUR SHOULDER WIDTH FROM SHOULDER SEAM TO SHOULDER SEAM, WEARING YOUR BEST FITTING SHIRT OR BLAZER. FOLLOW THE CURVE IN YOUR SHOULDER.	
3.	SLEEVE LENGTH		MEASURE SLEEVE LENGTH FROM SHOULDER SEAM, TO JUST ABOVE THE BASE OF YOUR THUMB. BOTH LEFT & RIGHT SLEEVE.	L R



4.	BICEP – MEASURE LEFT AND RIGHT		MEASURE AROUND THE CENTER OF YOUR ARM. DO NOT CONTRACT YOUR BICEP MUSCLE "NO FLEXING".	L R
5.	WRIST – MEASURE LEFT AND RIGHT		MEASURE AROUND YOUR WRIST BONE.	
6.	CHEST		MEASURE AROUND THE FULLEST PART OF YOUR CHEST MAKING SURE THE TAPE SITS RIGHT ACROSS THE NIPPLE LINE.	
7.	STOMACH		MEASURE AROUND THE FULLEST PART OF YOUR STOMACH — IN A RELAXED POSITION DO NOT STICK YOUR STOMACH IN OUR OUT.	
8.	WAIST	13	MEASURE AROUND YOUR WAIST.	



9.	JACKET LENGTH		MEASURE FROM THE BASE OF YOUR NECK TO THE BOTTOM OF YOUR REAR-END.	
10.	SEAT		MEASURE AROUND THE FULLEST PART OF YOUR HIPS. BE SURE THE MEASURE TAPE SITS ON THE PART OF YOUR REAR- END THAT STICKS OUT THE MOST.	
11.	OUT-SEAM		MEASURE FROM THE TOP OF YOUR BEST FITTED PANTS TO THE BOTTOM WHERE THEY END.	
12.	CROTCH		MEASURE FROM THE TOP OF THE FRONT OF YOUR PANTS, BETWEEN YOUR LEGS TO THE BACK TOP OF YOUR PANTS.	
13.	THIGH – MEASURE LEFT AND RIGHT	Resident Services	MEASURE AROUND THE FULLEST PART OF YOUR THIGHS.	L R



14.	KNEE – MEASURE LEFT AND RIGHT		MEASURE AROUND YOUR KNEES.	
15.	INSEAM	INSEAM	MEASURE FROM THE BOTTOM OF YOUR CROTCH TO THE BOTTOM OF YOUR INNER PANT LEG, KEEP YOUR LEG STRAIGHT.	
16.	CUFF	A STATE OF THE STA	MEASURE THE DESIRED WIDTH OF YOUR PANT CUFF.	